

金格制冷

業務用飲料展示櫃目錄 Commercial Beverage Display Cabinet Catalogue



WWW.KINCO.COM.TW



Upright Refrigerator / Freezer Showcase

直立式冷凍/冷藏展示櫃



型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	冷媒 Refrigerant
CK-UG560C	640(w) x 800(d) x 2070(h)	+ 0°C ~ + 6°C	880W	R134A
CK-UG930C	1260(w) x 800(d) x 2070(h)	+ 0°C ~ + 6°C	1170W	R404A
CK-UG1800C	1860(w) x 800(d) x 2070(h)	+ 0°C ~ + 6°C	1110W	R404A
CK-UG560F	640(w) x 800(d) x 2070(h)	- 15°C ~ - 22°C	2000W	R404A
CK-UG930F	1260(w) x 800(d) x 2070(h)	- 15°C ~ - 22°C	1650W	R404A
CK-UG1800F	1860(w) x 800(d) x 2070(h)	- 15°C ~ - 22°C	2300W	R404A

- 低音運行
Low Voice
- 節能環保
Energy Saving
- 電壓 Voltage: 220-240V / 50/60HZ
- 風冷無霜
Frost-Free
- 快速製冷
Rapid Cooling
- 冷卻方式 Cooling Method: 風冷式 Air-cooled

*CK系列由中國工廠組裝
CK series are assembled by China factory





CK-JC280



CK-JC360



CK-UGF480

型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	冷媒 Refrigerant
CK-JC280	560(w) x 600(d) x 1780(h)	+ 0°C ~ + 6°C	480W	R134A
CK-JC360	600(w) x 630(d) x 1860(h)	+ 0°C ~ + 6°C	550W	R134A
CK-UGF480	670(w) x 700(d) x 1980(h)	-15°C ~ -22°C	880W	R134A



低音運行
Low Voice



節能環保
Energy Saving



電壓 Voltage: 220-240V / 50/60HZ



風冷無霜
Frost-Free



快速製冷
Rapid Cooling



冷卻方式 Cooling Method: 風冷式 Air-cooled

*CK系列由中國工廠組裝
CK series are assembled by China factory



Upright Refrigerator Showcase

直立式冷藏展示櫃



CK-JC860S / CK-JC980S



CK-JC1300S

型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	冷媒 Refrigerant
CK-JC600S	900(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	920W	R134A
CK-JC860S	1150(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1170W	R134A
CK-JC980S	1360(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1380W	R134A
CK-JC1300S	1750(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1650W	R134A
CK-JC600SF	900(w) x 650(d) x 1980(h)	-15°C ~ -22°C	1650W	R404A
CK-JC860SF	1150(w) x 650(d) x 1980(h)	-15°C ~ -22°C	2000W	R404A
CK-JC980SF	1360(w) x 650(d) x 1980(h)	-15°C ~ -22°C	2000W	R404A
CK-JC1300SF	1750(w) x 650(d) x 1980(h)	-15°C ~ -22°C	2300W	R404A



低音運行
Low Voice



節能環保
Energy Saving



電壓 Voltage: 220-240V / 50/60HZ



風冷無霜
Frost-Free



快速製冷
Rapid Cooling



冷卻方式 Cooling Method: 風冷式 Air-cooled

*CK系列由中國工廠組裝
CK series are assembled by China factory





*CK-JC860SDD 型號展示櫃可放 尺寸400MM x 600MM烤盤
Size 400MM x 600MM baking tray can be fitted in model CK-JC860SDD.

型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	冷媒 Refrigerant
CK-JC600SD	900(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	920W	R134A
CK-JC860SD	1150(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1170W	R134A
CK-JC980SD	1360(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1380W	R134A
CK-JC860SDD	1150(w) x 800(d) x 1980(h)	+ 0°C ~ + 6°C	1380W	R134A



低音運行
Low Voice



節能環保
Energy Saving



電壓 Voltage: 220-240V / 50/60HZ



風冷無霜
Frost-Free



快速製冷
Rapid Cooling



冷卻方式 Cooling Method: 風冷式 Air-cooled



*CK系列由中國工廠組裝
CK series are assembled by China factory

Upright Refrigerator Showcase
直立式冷藏展示櫃

金格制冷



*CK-JC1800SDD 型號展示櫃可放尺寸400MM x 600MM烤盤
Size 400MM x 600MM baking tray can be fitted in model CK-JC860SDD.

型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	冷媒 Refrigerant
CK-JC1800SD	1800(w) x 650(d) x 1980(h)	+ 0°C ~ + 6°C	1650W	R134A
CK-JC1800SDD	1800(w) x 800(d) x 1980(h)	+ 0°C ~ + 6°C	1650W	R134A



低音運行
Low Voice



節能環保
Energy Saving



電壓 Voltage: 220-240V / 50/60HZ



風冷無霜
Frost-Free



快速製冷
Rapid Cooling



冷卻方式 Cooling Method: 風冷式 Air-cooled

*CK系列由中國工廠組裝
CK series are assembled by China factory





Countertop Refrigerator / Freezer Showcase

桌上型冷凍/冷藏展示櫃



型號 Model	尺寸 (毫米) Dimension (mm)	溫度範圍 Temperature	耗電量 Electrical Consumption	容積 Capacity
CK-TGF50	500(w) x 450(d) x 800(h)	-15°C ~ -22°C	600W	50L
CK-TGR50	500(w) x 450(d) x 800(h)	+ 2°C ~ + 6°C	400W	50L



低音運行
Low Voice



節能環保
Energy Saving



電壓 Voltage: 220-240V / 50/60HZ



風冷無霜
Frost-Free



快速製冷
Rapid Cooling



冷卻方式 Cooling Method: 風冷式 Air-cooled

*CK系列由中國工廠組裝
CK series are assembled by China factory

